

Piaba West Drilling - 2017

Hole ID	From (m)	To (m)	Length (m)	Au (g/t)	Cut-off (g/t Au)	Target	Section	Length (m)	Dip	Azimuth
BRAZD563	43.00	44.00	1.00	0.72	0.3	Piaba Infill	1550W	180.7	-59	168
and	126.00	127.00	1.00	1.45	0.3					
and	137.00	156.00	19.00	0.97	0.3					
incl	149.00	151.00	2.00	2.69	1.0					
and	159.00	159.60	0.60	0.51	0.3					
BRAZD564	61.30	62.30	1.00	0.56	0.3	Piaba Infill	1500W	150.85	-72	168
and	81.00	84.10	3.10	2.77	0.3					
incl	82.00	83.00	1.00	5.74	0.1					
and	108.00	109.00	1.00	0.30	0.3					
and	110.00	116.00	6.00	1.37	0.3					
incl	110.00	112.00	2.00	2.60	1.0					
and	125.00	127.00	2.00	0.67	0.3					
BRAZD565	93.00	94.00	1.00	0.61	0.3	Piaba West	2100W	231	-54	168
and	101.00	104.00	3.00	0.49	0.3					
and	154.20	155.40	1.20	4.05	0.3					
and	163.00	167.60	4.60	3.31	0.3					
incl	163.00	166.40	3.40	4.20	1.0					
and	176.40	179.00	2.60	0.80	0.3					
and	201.00	202.00	1.00	0.33	0.3					
BRAZD566	37.00	38.00	1.00	2.51	0.3	Piaba West	2075W	217.55	-53	168
and	80.00	81.00	1.00	1.80	0.3					
and	99.00	100.00	1.00	0.39	0.3					
and	127.00	136.00	9.00	4.64	0.3					
incl	128.00	134.00	6.00	6.81	1.0					
BRAZD567	73.00	74.00	1.00	0.46	0.3	Piaba Infill	1550W	130.45	-54	168
and	77.00	78.00	1.00	0.30	0.3					
and	81.00	100.00	19.00	2.01	0.3					
incl	84.00	89.00	5.00	3.49	1.0					
incl	98.00	99.60	1.60	4.33	1.0					
and	104.00	108.20	4.20	0.64	0.3					
and	110.00	111.00	1.00	0.49	0.3					
BRAZD568	42.00	44.00	2.00	0.34	0.3	Piaba Infill	1400W	145.00	-64	168
and	66.30	67.00	0.70	0.57	0.3					
and	78.10	104.00	25.90	1.27	0.3					
incl	88.00	90.00	2.00	2.11	1.0					
incl	96.00	99.00	3.00	3.57	1.0					
and	107.00	113.00	6.00	0.37	0.3					
and	118.00	119.00	1.00	0.39	0.3					
and	121.00	123.00	2.00	3.09	0.3					
and	130.20	136.00	5.80	1.67	0.3					
incl	134.00	135.00	1.00	3.44	1.0					
BRAZD569	40.00	41.00	1.00	0.50	0.3	Piaba West	1900W	185.10	-55	168
and	71.00	72.00	1.00	0.31	0.3					
and	80.00	81.00	1.00	0.59	0.3					
and	136.00	137.00	1.00	15.30	0.3					
and	151.00	152.00	1.00	0.48	0.3					
BRAZD570	20.00	22.00	2.00	0.81	0.3	Piaba Infill	1650W	209.00	-60	168
and	26.00	27.00	1.00	0.41	0.3					
and	147.00	148.00	1.00	0.37	0.3					

and	163.00	168.00	5.00	0.33	1.0					
and	170.00	187.00	17.00	1.35	0.3					
incl	171.00	174.00	3.00	4.32	0.1					
and	193.00	194.00	1.00	0.54	0.3					
BRAZD571	45.00	46.00	1.00	0.44	0.3	Piaba West	2125W	239.15	-53	168
and	50.00	56.00	6.00	6.59	0.3					
incl	52.00	54.00	2.00	17.73	0.1					
and	68.00	73.00	5.00	7.32	0.3					
incl	68.00	69.00	1.00	8.60	1.0					
incl	71.00	72.00	1.00	8.10	1.0					
and	85.00	86.00	1.00	0.55	0.3					
and	104.00	106.00	2.00	0.79	0.3					
and	108.00	109.00	1.00	1.59	0.3					
and	175.00	177.00	2.00	0.54	1.0					
BRAZD572	20.00	22.00	2.00	0.48	0.3	Piaba West	2025W	187.65	-55	168
and	63.00	65.00	2.00	1.92	0.3					
and	124.00	125.00	1.00	0.33	0.3					
BRAZD573	52.00	54.00	2.00	1.22	0.3	Piaba Infill	1350W	142.80	-57	168
and	72.00	89.00	17.00	0.83	0.3					
and	93.00	101.00	8.00	1.84	0.3					
and	130.00	131.00	1.00	3.22	0.3					
and	140.00	141.00	1.00	0.52	0.3					
BRAZD574	4.00	5.00	1.00	0.34	0.3	Piaba West	1950W	183.95	-55	168
BRAZD575	97.00	102.00	5.00	0.49	0.3	Piaba West	2200W	221.35	-55	168
and	181.00	182.00	1.00	0.38	0.3					
and	186.00	187.00	1.00	0.30	0.3					
BRAZD576	84.00	85.00	1.00	0.43	0.3	Piaba Infill	1350W	127.25	-66	168
and	88.00	97.00	9.00	1.43	0.3					
incl	90.00	91.00	1.00	5.65	1.0					
and	102.00	103.00	1.00	0.49	0.3					
and	107.00	109.00	2.00	0.56	0.3					
and	113.00	123.00	10.00	1.32	0.3					
incl	120.00	121.00	1.00	5.44	1.0					
and	126.00	127.25	1.25	0.29	0.3					
BRAZD576A	91.00	92.00	1.00	0.43	0.3	Piaba Infill	1350W	180.95	-66	168
and	98.00	100.00	2.00	1.26	0.3					
and	106.00	112.00	6.00	0.46	0.3					
and	120.00	121.00	1.00	2.73	0.3					
and	126.00	128.00	2.00	0.61	0.3					
and	134.00	137.00	3.00	0.54	0.3					
and	140.00	141.00	1.00	0.39	0.3					
and	147.00	154.00	7.00	0.57	0.3					
BRAZD577	0.00	4.00	4.00	0.98	0.3	Piaba Infill	1700W	129.60	-77	168
and	38.00	45.00	7.00	2.82	0.3					
incl	39.00	44.00	5.00	3.52	0.1					
and	62.00	84.00	22.00	2.08	0.3					
incl	67.00	70.00	3.00	11.21	1.0					
and	117.10	123.00	5.90	0.49	0.3					
BRAZD579	11.00	15.00	4.00	0.37	0.30	Piaba West	2050W	154.8	-56	168
and	19.00	20.00	1.00	0.37	0.30					
and	23.00	24.00	1.00	0.31	0.30					
and	52.00	53.00	1.00	1.07	0.30					
and	55.00	56.00	1.00	0.30	0.30					
and	62.00	63.00	1.00	0.52	0.30					
and	73.00	81.00	8.00	3.44	0.30					
incl	73.00	76.00	3.00	8.02	1.00					
BRAZD580	3.00	4.00	1.00	2.32	0.30	Piaba Infill	1600W	194.25	-76	168
and	18.00	19.00	1.00	0.34	0.30					

and	29.00	30.00	1.00	0.76	0.30					
and	116.00	117.00	1.00	2.20	0.30					
and	126.00	129.00	3.00	0.68	0.30					
and	147.00	152.00	5.00	1.61	0.30					
and	158.00	159.00	1.00	0.94	0.30					
and	167.00	168.00	1.00	0.44	0.30					
BRAZD581	116.00	122.00	6.00	0.49	0.30	Piaba Infill	1450W	178.2	-60	168
and	126.00	137.00	11.00	1.11	0.30					
and	142.00	143.00	1.00	0.57	0.30					
and	146.00	147.00	1.00	0.89	0.30					
BRAZD582	28.00	29.00	1.00	0.32	0.30	Piaba West	1950W	171.5	-55	168
and	32.00	33.00	1.00	0.80	0.30					
and	77.00	78.00	1.00	0.41	0.30					
and	112.00	114.00	2.00	1.03	0.30					
and	123.00	124.00	1.00	0.33	0.30					
and	127.00	128.00	1.00	2.14	0.30					
and	136.00	137.00	1.00	0.65	0.30					
and	155.00	156.00	1.00	1.97	0.30					
BRAZD583	53.00	54.00	1.00	1.13	0.30	Piaba West	1900W	149.9	-53	168
and	109.00	111.00	2.00	0.33	0.30					
and	123.00	124.00	1.00	0.32	0.30					
BRAZD584	179.00	180.00	1.00	0.36	0.30	Piaba Infill	1500W	244.95	-76	168
and	184.00	194.00	10.00	2.12	0.30					
incl	187.00	190.00	3.00	4.13	1.00					
and	217.00	219.00	2.00	1.47	0.30					
BRAZD585	17.00	18.00	1.00	0.63	0.30	Piaba Infill	1750W	126.95	-66.19	168
and	53.00	55.00	2.00	0.61	0.30					
and	58.00	92.00	34.00	1.65	0.30					
incl	62.40	74.00	11.60	3.42	1.00					
and	96.00	98.00	2.00	0.76	0.30					
BRAZD586	45.00	79.00	34.00	1.03	0.30	Piaba West	1800W	116.85	-51	168
incl	55.00	57.00	2.00	6.43	1.00					
incl	72.00	73.00	1.00	4.73	1.00					
and	108.00	112.00	4.00	0.89	0.30					

#### Qualified Person and Disclosure Statement

Scott Heffernan, M.Sc., P.Geo., the Company's EVP Exploration and Qualified Person under National Instrument 43-101, has reviewed and verified that the technical information contained in this document is accurate and approves the written disclosure of the same. Drill composites were calculated using cut-off values of 0.3 g/t, 1.0 g/t or 5.0 g/t gold as specified in the drill table and contain no more than 3 metres of internal waste. Drill intersections are calculated using uncut assays and are reported as drilled thicknesses. True widths of the mineralized intervals are interpreted to be 60 to 90 percent of the reported lengths. All samples were submitted to ALS Chemex in Belo Horizonte, Brazil for sample preparation. Sample pulps were then sent to ALS Chemex in Lima, Peru for geochemical analysis for gold by fire assay of a 30-gram charge with an Atomic Absorption finish (AA) and for a 33 multi-element geochemical suite by 4-acid digestion and Inductively-Coupled Mass Spectrometry (ICP-MS). Samples with AA gold values over 10.0 g/t are re-assayed by Screen Metallics fire assay. Control samples (accredited standards, blanks and duplicate samples at the field and preparation stages) were inserted on a regular basis. Results were monitored upon receipt of assays.